



STARIS® E-SERIES

COMPACT. EASE OF SERVICE. COMMERCIAL PERFORMANCE.


FEATURES

UltraCut™ Series 3 Deck
Side Discharge: 32 | 36

Commercial-Grade Engine
Kawasaki®

Operator Comfort
Patented contoured operator support pad

Serviceability and Accessibility
Flip-up front cover and a rear panel that lifts and locks into place



SINGLE-POINT HEIGHT-OF-CUT
Operators can quickly and accurately change the cut height by simply adjusting the pin and raising or lowering the deck.



COMPACT DESIGN
The compact size of Staris reduces trailer and storage space; and gives you the ability to access more yards, more quickly, while providing exceptional maneuverability on tough terrain.

TOP ACCESSORIES

- 3-Bushel Bagger
- 12-Volt Power Port
- Equipment Cover
- LED Light Kit
- Micro-Mulch System
- Operator Control Discharge (Hand)
- Trash Container
- Strobe Light Kit

Accessories may not fit each mower model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

The commercial mowers more landscape pros trust.

exmark.com

STARIS E-SERIES

MODEL	ENGINE	SIZE	DECK	WEIGHT	DIMENSIONS (W X H X L)
STE600CKA323H1	FS600V Kawasaki	36"	UltraCut Series 3	725 lbs.	48.0" x 47.3" x 58.1"
STE600CKA363H1	FS600V Kawasaki	36"	UltraCut Series 3	779 lbs.	48.0" x 47.3" x 58.1"



Side Discharge



Side Discharge

POWER COMPONENTS

Engine – FS600V Kawasaki V-Twin; All engines governed to 3,600 rpm.

Air Filter – Standard Engine Manufacturer's air filter.

Drive System – Two Hydro-Gear 10cc pumps powering two Parker 12 cubic inch motors.

Hydro Fluid – Exmark Premium Hydro Oil.

Speed – Infinitely variable speed selection 0–7.5 mph (12.1 kmph) forward, 0–4.0 mph (6.4 kmph) reverse.

PTO Engagement – Warner 105 ft-lb clutch.

Fuel Capacity – 5-gallon (18.9-L), single fuel tank with single fill location.

Drive-Wheel Release – Allows unit movement without engine running.

Safety Package – Operator Presence Controls (OPC) with safety interlock system indicators.

Deck Lift – Single-point height-of-cut with mechanical lift-assist spring on H1 model.

DECK

Style – Full-floating UltraCut™ Series 3 on 32" and 36" units. Side-discharge standard with flexible discharge chute and option to bag or mulch.

Deck Construction – 7-gauge top that is formed and continuously seam welded, 7-gauge side skirt.

Widths Available – 32" (81.3 cm) and 36" (91.4 cm).

Cutting Height – 1.0" (2.54 cm) to 4.5" (12.7 cm) in 0.25" (1.27 cm) increments.

Blade Spindles – No maintenance, sealed and nongreasable spindles; 7.75" diameter cutter housing with 1.75" diameter splined blade driver 1.0"-diameter spindle shaft.

Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Tractor Frame – Welded, heavy-duty 1.5" x 3" tubular steel.

Suspension Platform – Adjustable operator platform suspension.

Steering and Motion Control – Twin levers with adjustable front reference bar to modify forward ground speed.

Casters – 0.38" thick caster yoke arms with sealed ball bearings.

Front Caster Tires – 9 x 4.50–5, smooth-tread, semi-pneumatic tires with sealed ball bearings.

Drive Tires – 21 x 7.00–10 Kenda tires on 32" unit; 21 x 8.50–10 Kenda drive tires on 36".

Turning Radius – True zero-turn.

Parking Brake – Lever-actuated bar brake.

Electrical – 12-volt sealed battery with 15-amp alternator.

Standard Features – Engine hour meter.

ACCESSORIES & OPTIONS

3-Bushel Bagger, 12-Volt Power Port, Accessory Adapter Kit, Equipment Cover, Hydro Maintenance Kit, LED Light Kit, Micro-Mulch System, Operator Controlled Discharge (Hand), Strobe Light Kit and Trash Container.

Accessories may not fit each model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

WARRANTY

Limited Warranty: 4-Year or 750 Hours (with No Hour Limit First 2 Years), 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

¹ Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut = 99 = acres per hour | 80% efficiency: MPH x width of cut ÷ 124 = acres per hour.

² For complete details, visit exmark.com or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Staris® are registered trademarks of Exmark Mfg. Co., Inc. ©2022 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2022. Rev 1.